CP Control Panel



Innovative Control Panel with Scalable Performance

- > Capacitive multi-touch
- > Display sizes: 7", 10.1" and 15.6"
- > IP65 aluminium front bezel, optional stainless steel
- > Stainless steel housing
- > CODESYS Soft-PLC



Multi-Touch Panels with Soft-PLC CODESYS®

This modern Control Panel series combines high-quality design with brilliant multi-touch technology displays and scalable performance. The Control Panels feature a robust glass touchscreen set within a stylish aluminium frame. Standard versions are considered for panel mount and offer IP65 protection at the front. The Control Panels can be delivered with the Soft-PLC CODE-SYS development tools for fast and efficient implementation of sophisticated automation and visualization solutions.

The Control Panel can be supplemented with Web Panels of the same design if several operator stations are required. For a flexible selection of performance levels Kontron provides single and dual core Arm® processors and offers multiple memory and storage options.

The systems have been designed as long-term available building blocks (> 10 years) and can also be customized and expanded for individual requirements.

Technical Information

DISPLAY		IPS, Optical bonded (7.0"), more features see table below
тоисн	TECHNOLOGY	PCAP, glossy glass surface
PROCESSOR	CPU	NXP Arm® i.MX6 1-2 Cores, 800 MHz
MEMORY/STORAGE	DRAM DDR3L eMMC NAND/NOR-FLASH SRAM/FRAM SD-CARD	1 GByte, soldered (up to 2 GByte) (4 to 16 GByte) 512 MByte (256 MByte) / 1 MByte (up to 16 MByte) 128 kByte (up to 512 kByte)/ (up to 512 kByte) microSD, exchangeable (up to 32 GByte SDHC)
INTERFACES	USB ETHERNET CAN SERIAL PORTS EXPANSION PLUGS (INTERNAL)	2x USB 2.0 (Host) 2x Ethernet (10/100) independent 1x CAN (isol.) 2x RS232, 1x RS485 (isol.) GPIO, HDMI, SPI, i ² C
MECHANICAL	CONSTRUCTION COOLING MOUNTING	Front IP65 in aluminium, backside IP20 in stainless steel Fanless Fixing elements for easy and quick cabinet mounting
ENVIRONMENT	CERTIFICATION POWER EMC OPERATING TEMPERATURE STORAGE TEMPERATURE HUMIDITY ALTITUDE	CE 24 VDC +-20 % EN 61000-6-2 (immunity), EN 61000-6-4 (emission) 0 °C +55 °C -20 °C +70 °C 10 %-90 % @ 39 °C, non-condensing Up to 6.500 ft (2000 m)
SOFTWARE	OPERATING SYSTEM SOFT-PLC (OPTION) PROTOCOLS (OPTION)	Embedded Linux (Yocto distribution) CODESYS V3 EtherCAT, Modbus TCP/RTU, Profinet, Ethernet IP, CANopen, OPC UA

Display Informationen

DISPLAY SIZE	RESOLUTION	FORMAT	BRIGHTNESS	DIMENSIONS	VIEWING ANGLE	COLORS	WEIGHT	CONSUMPTION
CP-70: 7.0"	1024x600	17:10	450 cd/m ²	200 x 132 x 48	85°/85°/85°/85°	16.7 million	~ 0.83 kg	5.5 VA
CP-101: 10.1"	1280×800	16:10	420 cd/m ²	265 x 187 x 41	85°/85°/85°/85°	16.7 million	~ 1.3 kg	8.9 VA
CP-156: 15.6"	1366x768	16:9	400 cd/m ²	405 × 254 × 60	85°/80°/85°/85°	16.7 million	~ 3.5 kg	16.8 VA



About Kontron

Kontron is a global leader in IoT/Embedded Computing Technology (ECT) and offers individual solutions in the areas of Internet of Things (IoT) and Industry 4.0 through a combined portfolio of hardware, software and services. With its standard and customized products based on highly reliable state-of-the-art technologies, Kontronprovides secure and innovative applications for a wide variety of industries. As a result, customers benefit from aceerated time-to-market, lower total cost of ownership, extended product lifecycles and the best fully integrated applications.

For more information, please visit: www.kontron.com

About Kontron Electronics

Kontron Electronics AG acts as a provider of automation solutions. The enterprise is at home in a variety of sectors, such as industrial machinery and device manufacturing, medical technology and building automation. Our portfolio includes proprietary and client-specific products, development and design services for complex electronics components, modules and systems, as well as production and assembly services for entire devices. The company is part of the technology corporation Kontron AG.

For more Information please visit: www.kontron-electronics.com

Your Contact

Kontron Electronics AG

Riedstrasse 1 CH-6343 Rotkreuz Tel.: +41 41 799 47 99 info@kontron.ch

www.kontron-electronics.com

Global Headquarters

Kontron Europe GmbH

Gutenbergstraße 2 85737 Ismaning, Germany Tel.: +49 821 4086-0 info@kontron.com

www.kontron.com

kontron